Miniature Speaker 32ohm, Mylar, 23mm dia.	Part No.	ABS-231-RC
	Page	1/5

1. ELECTRICAL AND ACOUSTICAL SPECIFICATION

	Item	Specifications
1-1	Dimension	Φ23×5.2t
1-2	Rated Input Power	0.5W
1-3	Max Input Power	1.0W
1-4	Rated Impedance	32±15% Ω /2KHz/1V
1-5	Resonance Frequency(f0)	800±20% Hz/1V
1-6	Sound Pressure Level	87±3 dB at (AVG 0.8,1.0,1.2,1.5)KHz 0.1W/0.1m baffleboard (IEC)
1-7	Frequency Range	FOHZ ~ 10KHz
1-8	Total Harmonic Distortion	5%MAX. at 1KHz, 0.5W
1-9	Flux Density	0.6T
1-10	Polarity	When a positive DC Current is applied to the voice coil terminal marked +or red ,the diaphram shall move forward
1-11	OperationTest	Must be normal at sine wave and program source 0.5W.
1-12	Buzz,Rattle,etc.	Should not be audible at 4.0V sine wave between (FO Hz ~ 10kHz)
1-13	Weight	4 g
1-14	Voice Coil Diameter	Φ10.4mm
1-15	Magnet (NdFeB)	Φ9.5×1.5t mm
1-16	Appearance	Should not exist any obstacle to be harmful to normal operation;damages,cracks,rusts and distortions,etc.

Alan Butcher Components
Alan Butcher Components Ltd
Unit 1 Beechwood Clump Farm Industrial Estate Tin Pot Lane Blandford Dorset DT11 7TD
Telephone 01258 456360 Email sales@abcomponents.co.uk
www.abcomponents.co.uk

2.ENVIRONMENTAL TEST

	Item	Specifications
2-1	High temp. Test	Keep 96 hours at +60℃±3℃ and leave 3 hours in normal temperature and then check
2-2	Low temp. Test	Keep 96 hours at -30℃±3℃ and leave 3 hours in normal temperature and then check
2-3	Humidity test	Keep 96 hours at + 40℃±3℃ relative humidity 95% and leave 3 hours in normal temperature and then checked.
2-4	Thermal cycle test.	Low temperature: -30℃±3℃, temperature:+60℃±3℃, cycle: 1 hour/cycle each, and then keep 5 cycles in a room.
2-5	Vibration	10~55~10Hz sin-wave sweep 15min. 5G(constant) X,Y, Z 3 direction. 2 hours each, total 6 hours.
2-6	Drop test	Free drop a unit from 100cm height to a board of 20mm thick x,y, z 6 direction. 1 times each, total 6 times.
2-7	Load test	Rated Power white noise is applied for 96 hours
2-8	Max Power test	Max power 1 min on – 2 min off 10 cycles.
2-9	Terminal strength test	Capable of withstand 1kg load for 15seconds without resulting in any damage or rejection.

PASS CRITERION :

After these test , the change of S.P.L shall be within ±3 dB .

Alan Butcher Components

Alan Butcher Components Ltd
Unit 1 Beechwood Clump Farm Industrial Estate Tin Pot Lane Blandford Dorset DT11 7TD
Telephone 01258 456360 Email sales@abcomponents.co.uk
www.abcomponents.co.uk

3.MEASURING METHOD(SPEAKER MODE)

3-1 .Test Condition

STANDARD

Temperature : 15 ~ 35℃

Relative humidity : 45% ~ 85%,

Atmospheric pressure : 860mbar to 1060mbar.

JUDGEMENT

Temperature : 20±3℃

Relative humidity : 60% ~ 70%,

Atmospheric pressure : 860mbar to 1060mbar

3-2 . Standard Test Fixture

1.Input Power : 0.1W(1.79V)

2.Zero Level : -dB

3.Mode : TSR

4.potentiometer Range : 50dB

5.Sweep Time : 0.5sec

Standard test condition of speaker



Alan Butcher Components

Alan Butcher Components Ltd
Unit 1 Beechwood Clump Farm Industrial Estate Tin Pot Lane Blandford Dorset DT11 7TD
Telephone 01258 456360 Email sales@abcomponents.co.uk
www.abcomponents.co.uk

SPECIFICATIONS	Part No.	ABS-231-RC
	Page	4/5

4.FREQUENCY RESPONSE CURVE



Alan Butcher Components

Alan Butcher Components Ltd
Unit 1 Beechwood Clump Farm Industrial Estate Tin Pot Lane Blandford Dorset DT11 7TD
Telephone 01258 456360 **Email** sales@abcomponents.co.uk
www.abcomponents.co.uk

SPECIFICATIONS	Part No.	ABS-231-RC
	Page	5/5

5.DIMENSIONS

Unless otherwise specified,tolerance:±0.3(unit:mm)



7	Front Gasket	1	Black Paper Gasket	GU-001
6	PCB	1	FR4	GU-001
5	Magnet	1	NdFeB	GU-001
4	Plate	1	SPCC	GU-001
3	Voice coil	1	Self-bonding wire	GU-001
2	Diaphragm	1	Black PET	GU-001
1	Frame	1	SPCC	GU-001
The material must be meet to GU-001				
PART NO.	PART NAME	Q'TY	MATERIAL	REMARK

Alan Butcher Components
Alan Butcher Components Ltd
Unit 1 Beechwood Clump Farm Industrial Estate Tin Pot Lane Blandford Dorset DT11 7TD
Telephone 01258 456360 Email sales@abcomponents.co.uk
www.abcomponents.co.uk