Microphone, Omnidirectional, 9.7mm dia., -40dB, leads & connector	Part No.	ABM-732-RC
	Page	1/5

A.SPECIFICATION

No.	Item	Unit	Specification	Condition
1	Directivity		Omnidirectional	
2	Sensitivity	dB	-40±2dB	F=1KHz 0dB=1V/Pa
3	Standard operating voltage	V	5	
4	Output impedance	Ω	1.5K	F=1KHz 1Pa
5	Operating voltage range	V	1.5 - 10	
6	Sensitivity reduction	dB	-3	At 3.0V to 1.5V
7	Frequency	Hz	50~16000Hz	
8	Max.current consumption	mA	0.5	
9	Signal to noise ratio	dB	60	F=1KHz 1Pa A weighted
10	Storage temp	℃	-25℃~+70℃	
11	Operating temp	℃	-20℃~+60℃	
12	Dimension	mm	Φ9.7×4.5	See appearance drawing 见外观图
13	Material		AL	
14	Terminal		Wire Type	See appearance drawing 见外观图

B.TYPICAL FREQUENCY RESPONSE CURVE



Alan Butcher Components

Alan Butcher Components Ltd
Unit 1 Beechwood Clump Farm Industrial Estate Tin Pot Lane Blandford Dorset DT11 7TD
Telephone 01258 456360 **Email** sales@abcomponents.co.uk
www.abcomponents.co.uk

C.APPEARANCE DRAWING&MEASUREMENT CIRCUIT



WIRE TYPE: UL1061#30AWG SHR-02V-S



Alan Butcher Components Ltd
Unit 1 Beechwood Clump Farm Industrial Estate Tin Pot Lane Blandford Dorset DT11 7TD
Telephone 01258 456360 Email sales@abcomponents.co.uk
www.abcomponents.co.uk

D. MECHANICAL CHARACTERISTICS

No.	Item	Test condition	Evaluation standard
1	Soldering Heat Resistance	Soldering iron of +330±5℃ should be placed on the terminal for 2±0.5 seconds.	No interference in operation
2	Vibration Test	The part shall be measured after being applied vibration of amplitude of 1.5mm with 10 to 55hz band of vibration frequency to each of 3 per-pendicular directions for 2 hours.	After any tests, the sensitivity to be within ±3dB of the initial sensitivity.
3	Drop Test	The microphone unit without packaged must be subjected to each 3 drops at three axises from the height of 1 meter to 20mm thick wooden board.	

Alan Butcher Components

Alan Butcher Components Ltd
Unit 1 Beechwood Clump Farm Industrial Estate Tin Pot Lane Blandford Dorset DT11 7TD
Telephone 01258 456360 Email sales@abcomponents.co.uk
www.abcomponents.co.uk

SPECIFICATIONS	Part No.	ABM-732-RC
	Page	5/5

E. ENVIRONMENTAL TEST

NO.	**Item**	Test conditions	Evaluation standard
1	High temp.test	After being placed in a chamber at +70℃ for 72 hours.	After any tests, the sensitivity to be within ±3dB of initial sensitivity after 6 hours of conditioning at +25℃
2	Low temp. test	After being placed in a chamber at -25℃ for 72 hours.	
3	Humidity test	After being placed in a chamber at +60℃and 90±5% relative humidity for 240 hours.	
4	Temp.cyle test	The part shall be subjected to 10 cycles. One cycle shall be consist of: 	

TEST CONDITION

Standard Test Condition: a)Temperature:+5~+35℃ b)Humidity:45-85% c)Pressure:860-1060mbar

Judgement Test Condition: a)Temperature:+25±5℃ b)Humidity:60-70% c)Pressure:860-1060mbar

Alan Butcher Components

Alan Butcher Components Ltd
Unit 1 Beechwood Clump Farm Industrial Estate Tin Pot Lane Blandford Dorset DT11 7TD
Telephone 01258 456360 Email sales@abcomponents.co.uk
www.abcomponents.co.uk